



SAFES

ROBUR I – ROBUR II – ROBUR III



Burglary protection

The safes are tested in accordance with the European standard EN-1143-1 and certified by SBSC.

Fire protection

The safes in models: 40, 50, 80, 500, 900, 1200 and 1500 are tested and classified in accordance with NT Fire 017 - 60P.

Description

Solid barrier material in the door and body.

Weight and measurement

See overleaf

Locking

As standard the safe is provided with one changeable key-lock type FAS/S&G 6890. Available as option:
Combination lock type S&G 8550MP,
Electronic combination lock type Wittkopp.

Finish

Off white, RAL 9010.

Fittings

See overleaf

Dimensions in mms and kilos

| Safe Robur I | | | | | | | | | |
|---------------------------------|-----------|-----------|-----------|------------|------------|-------------|-------------|---------------|---------------|
| Model | 40 | 50 | 80 | 500 | 900 | 1200 | 1500 | 1800/2 | 1800/3 |
| External measurements mm | | | | | | | | | |
| Height | 565 | 665 | 965 | 665 | 1065 | 1365 | 1665 | 1985 | 1985 |
| Width | 560 | 560 | 560 | 660 | 660 | 660 | 660 | 890 | 1210 |
| Depth * | 600 | 600 | 600 | 670 | 670 | 670 | 670 | 810 | 810 |
| Internal measurements mm | | | | | | | | | |
| Height | 400 | 500 | 800 | 500 | 900 | 1200 | 1500 | 1820 | 1820 |
| Width | 400 | 400 | 400 | 500 | 500 | 500 | 500 | 730 | 1050 |
| Depth | 330 | 330 | 330 | 400 | 400 | 400 | 400 | 540 | 540 |
| Weight kilos | 190 | 210 | 290 | 275 | 370 | 480 | 560 | 1000 | 1300 |
| Standard fittings | 1 shelf | 1 shelf | 2 shelves | 1 shelf | 2 shelves | 2 shelves | 3 shelves | 3 shelves | 3 shelves |

| Safe Robur II | | | | | | | | | |
|---------------------------------|-----------|-----------|-----------|------------|------------|-------------|-------------|---------------|---------------|
| Model | 40 | 50 | 80 | 500 | 900 | 1200 | 1500 | 1800/2 | 1800/3 |
| External measurements mm | | | | | | | | | |
| Height | 565 | 665 | 965 | 665 | 1065 | 1365 | 1665 | 1985 | 1985 |
| Width | 560 | 560 | 560 | 660 | 660 | 660 | 660 | 890 | 1210 |
| Depth * | 600 | 600 | 600 | 670 | 670 | 670 | 670 | 810 | 810 |
| Internal measurements mm | | | | | | | | | |
| Height | 400 | 500 | 800 | 500 | 900 | 1200 | 1500 | 1820 | 1820 |
| Width | 400 | 400 | 400 | 500 | 500 | 500 | 500 | 730 | 1050 |
| Depth | 330 | 330 | 330 | 400 | 400 | 400 | 400 | 540 | 540 |
| Weight kilos | 375 | 430 | 590 | 580 | 800 | 960 | 1140 | 1840 | 2170 |
| Standard fittings | 1 shelf | 1 shelf | 2 shelves | 1 shelf | 2 shelves | 2 shelves | 3 shelves | 3 shelves | 3 shelves |

| Safe Robur III | | | | | | | | | |
|---------------------------------|-----------|-----------|-----------|------------|------------|-------------|-------------|---------------|---------------|
| Model | 40 | 50 | 80 | 500 | 900 | 1200 | 1500 | 1800/2 | 1800/3 |
| External measurements mm | | | | | | | | | |
| Height | 565 | 665 | 965 | 665 | 1065 | 1365 | 1665 | 1985 | 1985 |
| Width | 560 | 560 | 560 | 660 | 660 | 660 | 660 | 890 | 1210 |
| Depth * | 600 | 600 | 600 | 670 | 670 | 670 | 670 | 810 | 810 |
| Internal measurements mm | | | | | | | | | |
| Height | 400 | 500 | 800 | 500 | 900 | 1200 | 1500 | 1820 | 1820 |
| Width | 400 | 400 | 400 | 500 | 500 | 500 | 500 | 730 | 1050 |
| Depth | 330 | 330 | 330 | 400 | 400 | 400 | 400 | 540 | 540 |
| Weight kilos | 400 | 460 | 620 | 610 | 835 | 1010 | 1200 | 1920 | 2250 |
| Standard fittings | 1 shelf | 1 shelf | 2 shelves | 1 shelf | 2 shelves | 2 shelves | 3 shelves | 3 shelves | 3 shelves |

* External depth
+ 55 mm for handle

INTERIOR FITTINGS




Lockable drawer



Lockable cupboard




Combination lock
S&G 8550 MP



Extra shelf



Electronic pincode lock



Sliding frame



Security cupboard

| Interior fittings | External height mm |
|-------------------------------|--------------------|
| A. Shelf | - |
| B. Lockable cupboard, small | 155 |
| C. Lockable cupboard, large | 355 |
| D. Sliding frame for A4/folio | - |
| E. Security cupboard | 420 |
| F. Lockable drawer, small | 155 |
| G. Lockable drawer, large | 355 |

We reserve the right to alter the specification without prior notice.



Head office
Robur Safe AB
Lundbyvägen 8
SE-310 50 SLÖINGE
Phone: +46 346 260 260
Fax: +46 346 260 222

info@robursafe.com

www.robursafe.com