



## SAFES

### ROBUR VI-EX



#### **Burglary protection**

The safes are tested in accordance with the new European standard EN-1143-1.

The safes have also passed the explosive test and are certified as EX safes.

The safes are tested and certified in Grade VI-EX

#### **Fire protection**

The safes in models: 900, 1200 and 1500 are tested and classified in accordance with NT Fire 017 – 60P.

#### **Description**

The safes are constructed with a new barrier material in the door and body.

#### **Locking**

As standard the safe is provided with 2 changeable key locks type FAS/S&G 6890.

Available as option:

Electronic combination lock, Wittkopp TwinLock 7220.

#### **Finish**

Off white RAL 9010 with a matching control panel.






#### **Fittings**

See overleaf


#### **Weight and measurement**

See overleaf


# Dimensions in mms and kilos

Model	IV-EX - 900 V-EX - 900 VI-EX - 900	IV-EX - 1200 V-EX - 1200 VI-EX - 1200	IV-EX - 1500 V-EX - 1500 VI-EX - 1500	IV-EX - 1800/2 V-EX - 1800/2 VI-EX - 1800/2	IV-EX - 1800/3 V-EX - 1800/3 VI-EX - 1800/3
					
<b>External measurements, mm</b>					
Height	1260	1560	1860	2180	2180
Width	760	760	760	990	1310
Depth *	770	770	770	910	910
<b>Internal measurements, mm</b>					
Height	900	1200	1500	1820	1820
Width	500	500	500	730	1050
Depth	400	400	400	540	540
<b>Weight kilos</b>					
Grade VI-EX	1500	1850	2200	3500	4400
Standard fittings	2 shelves	2 shelves	3 shelves	3 shelves	3 shelves

\* External depth + 55 mm for handle



Lockable drawer



Lockable cupboard




Combination lock  
S&G 8550 MP



Extra shelf




Electronic pincode lock



Sliding frame



Security cupboard



## INTERIOR FITTINGS

Interior fittings	External height mm
A. Shelf	-
B. Lockable cupboard, small	155
C. Lockable cupboard, large	355
D. Sliding frame for A4/folio	-
E. Security cupboard	420
F. Lockable drawer, small	155
G. Lockable drawer, large	355

Safe type	A	C	R
900	660	475	678
1200	660	475	678
1500	660	475	678
1800/2	890	625	908
1800/3	1210	835	1228

We reserve the right to alter the specification without prior notice.



Head office

Robur Safe AB

Lundbyvägen 8  
SE-310 50 SLÖINGE  
Phone: +46 346 260 260  
Fax: +46 346 260 222

info@robursafe.com

www.robursafe.com