



SECURITY CABINETS SS 3492 ROBUR RSK



Use:

Amongst others for storage of: Documents Video films Cell-phones Cigarettes and Tobacco Weapons

Burglary protection

Robur Security Cabinets are tested and approved in accordance with the Swedish standard SS 3492.

Description

The body is a solid welded construction in 4 mm cold rolled steel. The door is in 4 mm steel, securely engaged on all four sides. The hinge side of the door is secured by means of a solid dog bolt independent of the hinges. All interior fittings can easily be moved every 50 mm. Prepared for anchoring to the floor.



Locking

As standard the Cabinet is provided with changeable key lock type FAS 6890. Available as option: Combination lock type S&G 8550MP, Electronic combination lock type Wittkopp.

Fittings

As standard the Cabinet is provided with adjustable shelves.

Colour

Light grey RAL 9002.

Storage of Computers and Data Equipment:

There is a special version of the Security Cabinet tested and approved for storing Data Equipment called RSKS. Please see a separate leaflet.

Measurements, weight and capacity


Model	RSK450	RSK 550/500	RSK700	RSK900	RSK1600	RSK1900	RSK1900/2
	@	•	@	•	e	e	P P
External dimensions mm Height Width Depth	450 480 480	550 500 380	700 600 480	900 475 490	1600 600 480	1900 750 480	1900 1000 480
Clear opening of the door mm Height Width	360 270	420 385	570 485	770 360	1470 485	1770 635	1770 900
Internal dimensions mm Height Width Depth	442 392 310	542 492 295	692 592 395	892 473 405	1592 592 395	1892 742 395	1892 992 395
Weight, kilos	50	62	100	110	180	220	290
Volume, litre	54	76	162	169	372	555	741
Adjustable shelves	1 shelf	1 shelf	1 shelf	2 shelf	3 shelves	4 shelves	4 shelves
Capacity of files	6	6	18	14	36	60	80
Capacity of cartons of cigarettes	appr. 30	appr. 40	appr. 90	appr. 95	appr. 230	appr. 330	appr. 450

Interior fittings



Electronic locks

Sliding frame for A4 folders



Extendable shelf

Extra shelf



Plate for keys



Box for data media

Capacity:	
3 ¹ / ₂ " Diskettes	appr. 105 pcs
4 mm DAT	appr. 30 pcs
8 mm DAT	appr. 18 pcs
DLT	appr. 12 pcs

We reserve the right to alter the specification without prior notice.



Head office Robur Safe AB

Lundbyvägen 8 SE-310 50 SLÖINGE Phone: +46 346 260 260 Fax: +46 346 260 222

info@robursafe.com