Atelier Boonen - Technomax DP



Additional information

brand: Technomax

Technomax DP – Fire-resistant private safe (EN 15659 LFS 30P, Security level S2)

The Technomax DP is a fire-resistant private safe, certified according to EN 15659 – LFS 30P: paper documents remain protected for 30 minutes at temperatures up to 850 °C. The safe is also tested for burglary resistance according to EN 14450, Security level S2.

The Technomax DP is built with a double-walled steel construction, filled with fire-resistant insulation, with a door and frame in 10 mm steel and a thermally insulating door seal. Thanks to the internal hinges, nothing protrudes on the hinge side, resulting in a clean design. The door opens 90°.

Depending on the model, the safe is equipped with:

- a double-bitted key lock (DPK),
- a double-bitted key lock combined with a mechanical combination lock with three dials (DPD) — the safe only opens with the key when the three dials show the correct code,
- or an electronic code lock with emergency power terminals and emergency key (DPE).

All locks are integrated flush into the door; only on the DPD do the code dials protrude by about 10 mm.

The safe is prepared for anchoring through one anchoring hole in the base and one in the back wall; fixing materials are included. If you are looking for the same safe without fire protection, see the Technomax Gold free-standing safes. Available in three formats from 13 to 39 litres.

See also our other fire resistant safes or read how to approach buying a safe in Belgium, with delivery and installation by our own team.

Fire resistant 30 min for paper

Burglary resistant according to EN 14450, Security level S2
Indication value storage Security level S2: € 5 000 cash or € 9 000 valuables

- Tested and certified against burglary according to EN 14450, Security level S2.
- Fire tested for 30 minutes for paper according to EN 15659 LFS 30P.
- Door and frame in 10 mm steel; double-walled body, filled with fire-resistant insulation.
- Three-sided locking, reinforced hinges on the inside of the safe.
- DPK with double-bitted key lock.
- DPD with double-bitted key lock and mechanical combination lock with three dials; opening is only possible with the key when the code is correct.
- DPE with electronic code lock on batteries, with emergency power terminals and a double-bitted emergency key lock.
- Locks integrated flush; only on the DPD do the code dials protrude by ± 10 mm.
- One anchoring hole in the base and one in the back wall, fixing materials included.
- Colour: dark grey.

Model specifications

Model	Outer dimensions (mm)	Internal dimensions (mm)	Volume (L)	Weight (kg)	Shelves
Technomax DPK 4	H280 W400 D355	H170 W305 D245	13 L	34 kg	0
Technomax DPK 5	H350 W490 D430	H240 W380 D310	24 L	52 kg	1
Technomax DPK 7	H490 W430 D430	H380 W330 D310	39 L	64 kg	1
Technomax DPD 4	H280 W400 D355	H170 W305 D245	13 L	34 kg	0
Technomax DPD 5	H350 W490 D430	H240 W380 D310	28 L	52 kg	1
Technomax DPD 7	H490 W430 D430	H380 W330 D310	39 L	64 kg	1
Technomax DPE 4P	H280 W400 D355	H170 W305 D245	13 L	34 kg	0
Technomax DPE 5P	H350 W490 D430	H240 W380 D310	28 L	52 kg	1
Technomax DPE 7P	H490 W430 D430	H380 W330 D310	39 L	64 kg	1