Atelier Boonen - Salvus Palermo



Additional information

brand: Salvus safes

Salvus Palermo – Certified burglary- and fire-resistant home safe (EN 14450 S2, LFS 30P)

The Salvus Palermo is a compact home safe, tested and certified by ECB·S according to the European standard EN 14450, Security level S2 for burglary resistance. This model additionally offers 30 minutes of fire protection for paper, tested in accordance with EN 15659 – LFS 30P. This standard provides protection up to 850 °C, without a drop test or cooling phase, and is intended for situations with limited fire risk.

The safe has a multi-walled construction with a fire-resistant filling. The door is locked on four sides: three sides with solid chrome-plated steel bolts and, on the hinge side, a rectangular bolt that engages into the body. The construction features anti-drill armour at the level of the lock and boltwork. The hinges allow a door opening of up to 180° and protrude 28 mm.

Depending on the model, this burglary- and fire-resistant home safe is fitted with an EN 1300 certified double-bitted key lock or an electronic code lock. The electronic lock has a flat design protruding only 15 mm; emergency power terminals are provided on the outside of the keypad and the battery is located on the inside of the door.

The Salvus Palermo is available in four sizes from 18 to 78 litres, each with a shelf and provided as standard with anchoring holes in the base and back wall.

See also our other fire resistant safes or read how to approach buying a safe in Belgium, with delivery and installation by our own team.

Fire resistant 30 min for paper
Burglary resistant according to EN 14450, Security level S2
Indication value storage Security level S2: € 5 000 cash or € 9 000 valuables

- Tested and certified by ECB·S in accordance with the European standard EN 14450, Security level S2.
- Fire tested for 30 minutes for paper according to EN 15659 LFS 30P.
- Multi-walled construction with a fire-resistant filling.

- Four-sided locking: chrome-plated steel bolts on three sides and a rectangular bolt on the hinge side, engaging into the body.
- Anti-drill armour at the level of the lock and boltwork.
- Hinges with door opening up to 180°; protruding 28 mm.
- Double-bitted key lock (EN 1300) or electronic code lock with flat design (15 mm), depending on the model.
- Height-adjustable shelves.
- Anchoring holes provided as standard in the base and back wall.
- Colour: anthracite grey RAL 7024.

Model specifications

Model	Outer dimensions (mm)	Internal dimensions (mm)	Volume (L)	Weight (kg)	Shelves
Salvus Palermo 1K	H315 W445 D440	H185 W334 D290	18 L	52 kg	1
Salvus Palermo 2K	H460 W440 D440	H330 W329 D290	31 L	68 kg	1
Salvus Palermo 3K	H670 W440 D440	H540 W329 D290	51 L	91 kg	1
Salvus Palermo 4K	H950 W440 D440	H820 W329 D290	78 L	120 kg	2
Salvus Palermo 1E	H315 W445 D440	H185 W334 D290	18 L	52 kg	1
Salvus Palermo 2E	H460 W440 D440	H330 W329 D290	31 L	68 kg	1
Salvus Palermo 3E	H670 W440 D440	H540 W329 D290	51 L	91 kg	1
Salvus Palermo 4E	H950 W440 D440	H820 W329 D290	78 L	120 kg	2