

## Atelier Boonen - Salvus Bologna - Fire-resistant safe



### Additional information

Salvus Bologna - fire-resistant safe class I (LFS 60P)

The Salvus Bologna is a fire-resistant safe with additional burglary resistance certification, designed for the protection of paper documents in applications with a medium risk profile. This model is certified in accordance with EN 1143-1 class I (ECB-S) and tested for fire resistance according to the European standard EN 15659 – LFS 60P.

Fire resistance according to LFS 60P ensures that documents remain protected for 60 minutes at furnace temperatures of up to 850 °C. This standard belongs to the lighter European fire test classifications and does not include a drop test or a natural cooling phase. The Salvus Bologna is therefore suitable for use in residential, office and administrative environments where the fire risk is considered moderate.

The safe is constructed with a robust steel body and is equipped with a three-sided locking system using solid steel bolts. On the hinge side, an internal anchoring profile is integrated, ensuring that attacks on the hinges have no effect on the locking mechanism. The door opens to 180° and the interior is fitted as standard with adjustable shelves.

With regard to the locking system, the Salvus Bologna can be equipped with EN 1300-certified locks,

including a double-bitted key lock, a mechanical combination lock or an electronic keypad lock. From model 67 onwards, a two-lock configuration is possible, allowing different lock types to be combined.

The fire-resistant safe is prepared for floor anchoring. Within the segment of class I fire-resistant safes, the Salvus Bologna is frequently selected for its combination of certified burglary resistance, fire protection in accordance with LFS 60P and a favourable price-performance ratio.

---

If you want, I can next:

Fireproof 60 min for paper

Burglary resistant class 1

Indication of value storage class 1: € 10 000 cash or € 20 000 valuables

- Tested and certified by ECB.S in accordance with European standard EN 1143-1 Grade I
- Fire-resistant tested 60 minutes for paper according to EN 15659 LFS 60P
- Three-sided locking by means of steel bolts
- Hook-in profile on the hinge side
- Standard equipped with double bit key lock
- Height adjustable shelves
- Prepared for anchoring
- Color: anthracite gray RAL 7024

## Model specifications

Model	Outer dimensions (mm)	Internal dimensions (mm)	Volume (L)	Weight (kg)	shelves
<a href="#">46</a>	H490 W480 D445	H330 W332 D295	33 L	106 kg	1
<a href="#">67</a>	H670 W480 D445	H510 W332 D295	49 L	136 kg	1
<a href="#">95</a>	H980 W545 D445	H820 W400 D295	94 L	205 kg	1
<a href="#">133</a>	H1336 W701 D580	H1142 W527 D388	233 L	413 kg	2
<a href="#">165</a>	H1652 W701 D580	H1459 W527 D388	298 L	501 kg	3