

Atelier Boonen - Sistec Euroguard SE 4 and 5



Additional information

brand: Sistec safes

Sistec Euroguard SE - Burglary-resistant safe Grade 4 or 5

The Sistec Euroguard SE is a high-security safe certified for burglary resistance, designed for applications requiring a high to very high level of protection against burglary. This range is tested according to EN 1143-1 and available in Grade 4 and Grade 5, with ECB-S approval. The Euroguard SE Grade 4 and 5 is designed for the secure storage of valuables, intensive use and situations where increased resistance to targeted burglary attempts is required.

The safe features a multi-walled body and door, constructed with high-quality barrier materials. The door is equipped with four-sided locking: three sides close with mobile, solid steel bolts. On the hinge side, fixed bolts provide additional anchoring into the safe body. As a result, attacks on the hinges have no effect on the security.

The locking mechanism is protected by multiple layers of armour over the locks and boltwork. A glass-plate relocker activates automatically in the event of tampering or attack and blocks the locking mechanism when manipulation is attempted.

The models offered by Atelier Boonen are supplied in the KB version. KB refers to **Kronenbohrer** / core drilling protection and indicates additional protection against attacks using diamond core drills (CD – Core Drilling).

Each Sistec Euroguard SE Grade 4 or 5 is equipped as standard with two EN 1300-certified locks, in

accordance with the requirements of EN 1143-1 for Grade 4 and Grade 5. Depending on the selected configuration, this can consist of a double-bit key lock and a mechanical combination lock. Optional electronic or mechanical combination locks, or a combination of both, are available.

The Euroguard SE Grade 4 and 5 stands out for its solid construction, refined finish and high-quality execution, making it suitable for intensive professional use. External hinges allow a door opening of up to 180°. The safe is prepared for anchoring through the base and rear wall and is supplied with adjustable shelves and a RAL 7035 light grey finish. Model 180 is supplied as a double-door safe.

Burglary resistant class 4,5

Indicated value retention class 4: € 75 000 cash or € 150 000 valuables

Indicated value retention class 5: € 125 000 cash or € 250 000 valuables

- Tested and certified by ECB-S according to the European standard EN 1143-1, Grades IV and V
- KB version with additional protection against attacks using diamond core drills (CD – Core Drilling)
- Multi-walled body and door construction, built with high-quality barrier materials for certified burglary resistance
- Four-sided door locking: three sides with mobile, solid steel bolts and fixed bolts on the hinge side
- The fixed bolts on the hinge side make attacks on the hinges, such as cutting or removal, ineffective
- Locks and boltwork are protected by additional armour and relocking systems, including a glass-plate relocker
- Equipped as standard with two EN 1300 Class B-certified locks: a double-bit key lock and a mechanical combination lock
- Model 180 is supplied as a double-door safe
- Height-adjustable shelves
- Prepared as standard for floor anchoring
- Colour: light grey RAL 7035

Model specifications

Model	Outer dimensions (mm)	Internal dimensions (mm)	Volume (L)	Weight (kg)	Shelves
SISTEC Euroguard SE IV KB 86/0	H860 W620 D580	H680 W450 D340	99 L	585 kg	1
SISTEC Euroguard SE IV KB 103	H1030 W620 D580	H850 W450 D340	124 L	690 kg	2
SISTEC Euroguard SE IV KB 120	H1200 W620 D580	H1020 W450 D340	149 L	710 kg	2
SISTEC Euroguard SE IV KB 121	H1200 W825 D700	H1200 W825 D460	297 L	1010 kg	2
SISTEC Euroguard SE IV KB 138	H1380 W825 D700	H1200 W655 D460	349 L	1170 kg	3
SISTEC Euroguard SE IV KB 173	H1730 W825 D700	H1550 W655 D460	451 L	1380 kg	4
SISTEC Euroguard SE IV KB 180	H1800 W1190 D730	H1620 W1020 D490	735 L	1892 kg	4

Model	Outer dimensions (mm)	Internal dimensions (mm)	Volume (L)	Weight (kg)	Shelves
SISTEC Euroguard SE V KB 86	H860 W620 D580	H680 W450 D340	99 L	610 kg	1
SISTEC Euroguard SE V KB 103	H1030 W620 D580	H850 W450 D340	124 L	710 kg	2
SISTEC Euroguard SE V KB 120	H1200 W620 D580	H1020 W450 D340	149 L	790 kg	2
SISTEC Euroguard SE V KB 121	H1200 W825 D700	H1020 W655 D460	297 L	1060 kg	2
SISTEC Euroguard SE V KB 138	H1380 W825 D700	H1200 W655 D460	349 L	1210 kg	3
SISTEC Euroguard SE V KB 173	H1730 W825 D700	H1550 W655 D460	451 L	1460 kg	4

Model	Outer dimensions (mm)	Internal dimensions (mm)	Volume (L)	Weight (kg)	Shelves
SISTEC Euroguard SE V KB 180	H1800 W1190 D730	H1620 W1020 D490	735 L	1960 kg	4