Atelier Boonen - Robur Depositsafe



Additional information

brand: Robur safes

Robur deposit safes – Grade 2, 3 or 4 with automatic blocking mechanism (EN 1143-2)

The Robur deposit safes are among the most secure on the market. Tested and certified according to EN 1143-2, they are available as a Grade 2, Grade 3 or Grade 4 deposit safe (D2, D3 and D4) — suited to applications with high demands on the protection of cash values.

Unlike conventional deposit safes, where an unlocked drawer is often a vulnerable point, Robur integrates an intelligent blocking mechanism into the deposit drawer. In the event of attempted manipulation, the armoured rear wall of the drawer locks automatically, effectively preventing access to the contents of the safe.

Even when the drawer is not locked, no one can reach the interior of the safe through the deposit system. This makes these models ideal for situations where staff need to deposit without having access to the actual safe compartment. The safes are equipped as standard with two key locks (door and drawer), but can be supplied with electronic combination locks on request. The deposit opening can be positioned at

the front, side or rear, and the door is also available left-hinged. Like the Robur I to V safes, the deposit safes are built from the UHPC composite developed by Robur.

The safes are finished in pearl white and prepared for anchoring. Available in various models and volumes.

See also our other deposit safes or read how to approach buying a safe in Belgium, with delivery and installation by our own team.

Burglary resistant class D2 to D4 (EN 1143-2)
Indicative value retention class D2: € 25 000 cash or € 50 000 valuables
Indicative value retention class D3: € 45 000 cash or € 90 000 valuables
Indicative value retention class D4: € 75 000 cash or € 150 000 valuables

- Fully certified deposit safe, tested by ECB·S in accordance with the European standard EN 1143-2, in Grades D2 to D4. The deposit function does not affect the indication value retention of the safe.
- Deposit system equipped with an anti-fishing device that prevents reaching the deposited values.
- Deposit drawer with passive relocking system: in the event of a burglary attempt, the armoured rear wall of the drawer blocks automatically.
- Door and body built from a UHPC composite developed by Robur, reinforced with various burglary-delaying armatures.
- Very heavy locking with solid steel bolts and a reinforced hook profile on the hinge side; the boltwork is additionally protected by armour plates and a double-acting blocking system.
- Drawer and door equipped as standard with a recodable S&G FAS double-bitted key lock; electronic combination locks on request.
- Deposit opening can be positioned at the front, side or rear of the safe.
- Door also available left-hinged.
- Anchoring holes provided in the base.
- Colour: pearl white.

Model specifications

Model	Outer dimensions (mm)	Internal dimensions (mm)	Volume (L)	Weight (kg)	Shelves
40 II	H720 W560 D600	H400 W400 D330	53 L	455 kg	0
50 II	H820 W560 D600	H500 W400 D330	57 L	510 kg	0
80 II	H1120 W560 D600	H600 W400 D330	106 L	670 kg	0
500 II	H835 W660 D670	H500 W500 D400	100 L	660 kg	0
900 II	H1235 W660 D670	H900 W500 D400	180 L	890 kg	0

Model	Outer dimensions (mm)	Internal dimensions (mm)	Volume (L)	Weight (kg)	Shelves
40 III	H720 W560 D600	H400 W400 D330	53 L	455 kg	0
50 III	H820 W560 D600	H500 W400 D330	57 L	510 kg	0
80 III	H1120 W560 D600	H800 W400 D330	106 L	670 kg	0
500 III	H835 W660 D670	H500 W500 D400	100 L	660 kg	0
900 III	H1235 W660 D670	H900 W500 D400	180 L	890 kg	0

Model	Outer dimensions (mm)	Internal dimensions (mm)	Volume (L)	Weight (kg)	Shelves
500 IV	H880 W690 D730	H500 W500 D400	100 L	900 kg	0
900 IV	H1280 W960 D730	H900 W500 D400	180 L	1160 kg	0