

Atelier Boonen - Salvus Rome



Additional information

brand: Salvus safes

Salvus Rome - Burglary- and fire-resistant safe (class 3, LFS 30P)

The Salvus Rome is a certified burglary- and fire-resistant safe, tested in accordance with EN 1143-1 class 3. Safes and strongrooms certified to this standard provide a reliable level of burglary resistance for applications with a medium risk profile.

The safe is tested in accordance with EN 15659 – LFS 30P and provides fire protection for paper documents at temperatures of up to 850 °C for 30 minutes.

The construction features a multi-wall steel structure, with the interspaces filled with Ultra High Performance Concrete (UHPC). This design ensures solid mechanical resistance within the certified segment.

The door is equipped with a three-sided locking system using solid steel bolts. On the hinge side, an internal interlocking profile is integrated, rendering attacks on the hinges ineffective. The Salvus Rome is also fitted with a passive relocking system with a glass plate. In the event of a targeted attack on the lock or the door, this glass plate automatically activates the blocking mechanism, securing the locking system.

In accordance with EN 1143-1, the Salvus Rome is standard equipped with at least one EN 1300-certified

class B lock. Depending on the configuration, the safe can also be fitted with two locks. Available lock types include double-bitted key locks, mechanical combination locks and electronic keypad locks, or a combination thereof.

The Salvus Rome is available in multiple versions with capacities ranging from 14 to 379 litres and is standard prepared for floor and wall anchoring.

Within the Salvus Rome range, the Salvus Rome Mini is also available. This very compact model is likewise certified to EN 1143-1, but is not fire-resistant. The Salvus Rome Mini is intended for applications where space is highly limited and only burglary protection is required.

Fireproof 30 min for paper

Burglary-resistant Class 3

Indication of Class 3 value retention: € 45 000 cash or € 90 000 valuables

- Tested and certified by ECB.S in accordance with European standard EN 1143-1 in Grade III
- Fire resistant tested 30 minutes for paper according to EN 15659 LFS 30P
- Multi-walled construction of walls and door.
- Three-sided locking by stainless steel bolts.
- Hook-in profile on hinge side.
- Standard equipped with double bit key lock
- Shelves adjustable in height
- Anchor holes provided in back and bottom
- Color: anthracite grey RAL7024

Model specifications

Model	Outer dimensions (mm)	Internal dimensions (mm)	Volume (L)	Weight (kg)	Shelves
Salvus Rome Mini	H350 W440 D350	H250 W340 D168	14 L	137 kg	0

Model	Outer dimensions (mm)	Internal dimensions (mm)	Volume (L)	Weight (kg)	Shelves
Salvus Rome 1	H500 W510 D510	H373 W395 D327	48 L	228 kg	1
Salvus Rome 2	H610 W680 D510	H483 W565 D327	104 L	309 kg	1
Salvus Rome 3	H670 W510 D510	H544 W395 D327	70 L	281 kg	1
Salvus Rome 4	H810 W680 D510	H683 W565 D327	126 L	396 kg	2
Salvus Rome 5	H990 W510 D510	H863 W395 D327	129 L	366 kg	2
Salvus Rome 6	H1010 W680 D510	H883 W565 D327	163 L	478 kg	2
Salvus Rome 7	H1200 W850 D660	H1053 W715 D467	387 L	779 kg	2
Salvus Rome 8	H1320 W680 D510	H1193 W565 D327	247 L	559 kg	3
Salvus Rome 9	H1320 W850 D510	H1173 W715 D327	295 L	719 kg	3
Salvus Rome 10	H1510 W850 D660	H1363 W715 D467	497 L	945 kg	3
Salvus Rome 11	H1510 W850 D600	H1363 W715 D407	435 L	881 kg	3
Salvus Rome 12	H1660 W680 D510	H1513 W545 D327	292 L	747 kg	4
Salvus Rome 13	H1660 W850 D510	H1513 W715 D327	379 L	873 kg	4