Atelier Boonen - Robur I, II, III, IV and V safes



Additional information

brand: Robur safes

Robur Safes – Swedish-made safes with certified burglary and fire protection (Grades I–V)

Robur Safe AB, based in Sweden, designs and manufactures high-security safes for demanding professional environments. The safes are certified to EN 1143-1 (Grades I to V, ECB·S / SBSC) and offer 60 minutes of fire protection for paper documents, tested according to the NT FIRE 017 – 60P standard.

Each safe is built with a robust multi-wall construction and features a passive relocking system that activates automatically in the event of an attack.

Depending on security requirements, the safes can be equipped with EN 1300-certified locks, including key locks, mechanical or electronic code locks, time-delay locks, or a combination of two locking systems for enhanced protection.

Interior configurations are fully customisable, with available options such as adjustable shelves, lockable

inner compartments, deposit drawers for quick deposits (available in Grades II to IV), pull-out frames and media drawers.

For high-risk applications, Robur also offers a separate Grade VI model with reinforced protection against explosives and core drilling.

See also our other fire resistant safes or read how to approach buying a safe in Belgium, with delivery and installation by our own team.

Fire rated 60 min for paper
Burglary resistant class 1,2,3,4,5
Indicative value retention class 1: € 10 000 cash or € 20 000 valuables
Indicative value retention class 2: € 25 000 cash or € 50 000 valuables
Indicative value retention class 3: € 45 000 cash or € 90 000 valuables
Indication value retention class 4: € 75 000 cash or € 150 000 valuables
Indication value retention class 5: € 125 000 cash or € 250 000 valuables

- Tested and certified by ECB·S/SBSC in accordance with European standard EN 1143-1 Grades I, II, III, IV and V.
- Fire resistant tested 60 minutes for paper according to NT 017 60 Paper
- Solid locking by means of rectangular steel bolts
- Hook-in profile on the hinge side
- Standard equipped with a double bit key lock up to class 3, from class 3 with an additional mechanical code lock.
- Height adjustable shelves
- Prepared for anchoring
- Color: white

Model specifications

Model	Outer dimensions (mm)	Internal dimensions (mm)	Volume (L)	Weight (kg)	Shelves
I-40	H558 W535 D531	H425 W400 D330	53 L	185 kg	1
I-50	H633 W535 D531	H500 W400 D330	66 L	200 kg	1
I-80	H933 W535 D531	H800 W400 D330	105 L	240 kg	2
I-500	H633 W635 D601	H500 W500 D400	100 L	220 kg	1
I-900	H1033 W635 D601	H900 W500 D400	180 L	360 kg	2
I-1200	H1333 W635 D601	H1200 W500 D400	240 L	440 kg	2
I-1500	H1623 W635 D601	H1490 W500 D400	300 L	520 kg	3

Model	Outer dimensions (mm)	Internal dimensions (mm)	Volume (L)	Weight (kg)	Shelves
II-40	H565 W560 D600	H400 W400 D330	53 L	385 kg	1
II-50	H665 W560 D600	H500 W400 D330	66 L	435 kg	1
II-80	H965 W560 D600	H800 W400 D330	105 L	590 kg	2
II-500	H665 W660 D670	H500 W500 D400	100 L	530 kg	1
II-900	H1065 W660 D670	H900 W500 D400	180 L	775 kg	2
II-1200	H1365 W660 D670	H1200 W500 D400	240 L	930 kg	2
II-1500	H1665 W660 D670	H1500 W500 D400	300 L	1100 kg	3

Model	Outer dimensions (mm)	Internal dimensions (mm)	Volume (L)	Weight (kg)	Shelves
III-40	H565 W560 D600	H400 W400 D330	53 L	405 kg	1
III-50	H665 W560 D600	H500 W400 D330	66 L	455 kg	1
III-80	H965 W560 D600	H800 W400 D330	105 L	615 kg	2

Model	Outer dimensions (mm)	Internal dimensions (mm)	Volume (L)	Weight (kg)	Shelves
III-500	H665 W660 D670	H500 W500 D400	100 L	555 kg	1
III-900	H1065 W660 D670	H900 W500 D400	180 L	795 kg	2
III-1200	H1365 W660 D670	H1200 W500 D400	240 L	975 kg	2
III-1500	H1665 W660 D670	H1500 W500 D400	300 L	1155 kg	3

Model	Outer dimensions (mm)	Internal dimensions (mm)	Volume (L)	Weight (kg)	Shelves
IV-500	H695 W690 D730	H500 W500 D400	100 L	810 kg	1
IV-500 CD	H695 W690 D730	H500 W500 D400	100 L	810 kg	1
IV-900	H1095 W690 D730	H900 W500 D400	180 L	1070 kg	2
IV-900 CD	H1095 W690 D730	H900 W500 D400	180 L	1070 kg	2
IV-1200	H1395 W690 D730	H1200 W500 D400	240 L	1310 kg	2
IV-1200 CD	H1395 W690 D730	H1200 W500 D400	240 L	1310 kg	2
IV-1500	H1695 W690 D730	H1500 W500 D400	300 L	1550 kg	3
IV-1500 CD	H1695 W690 D730	H1500 W500 D400	300 L	1550 kg	3

Model	Outer dimensions (mm)	Internal dimensions (mm)	Volume (L)	Weight (kg)	Shelves
V-500	H695 W690 D730	H500 W500 D400	100 L	850 kg	1
V-500 CD	H695 W690 D730	H500 W500 D400	100 L	850 kg	1
V-900	H1095 W690 D730	H900 W500 D400	180 L	1110 kg	2
V-900 CD	H1095 W690 D730	H900 W500 D400	180 L	1110 kg	2
V-1500	H1695 W690 D730	H1500 W500 D400	300 L	1630 kg	3
V-1500 CD	H1695 W690 D730	H1500 W500 D400	300 L	1630 kg	3