

Atelier Boonen - Chubb safes DPC



Additional information

Chubb safes DPC – Fire-Resistant Document Storage (UL 72, 120 Minutes)

The Chubb safes DPC is a high-quality fire-resistant document safe, designed to protect paper documents from the devastating effects of fire. Certified according to the UL 72 Class 350 standard, it provides up to 120 minutes of fire protection at temperatures up to 1000°C, making it a reliable solution for securely storing important documents.

The Chubb safes DPC is available in six sizes ranging from 160 to 670 liters, offering ample capacity for large volumes of documents. Its advanced locking mechanism ensures that the safe remains fire-resistant as soon as the door is closed, while the interlocking door system on double-door models prevents accidental door openings.

This document safe is standardly equipped with a Mauer 7111A key lock, but offers the option of electronic or mechanical combination locks for added security and ease of use. For enhanced safety, the Chubb safes DPC can be optionally anchored to the floor to prevent theft and improve stability.

The DPC has been rigorously tested to meet strict fire resistance standards, with exposure to 1000°C for two hours followed by a cooling period. These tests simulate realistic fire conditions and ensure that the contents of the safe remain protected even after a fire. The Chubb safes DPC provides exceptional fire protection for documents and valuable papers, with the option to tailor the safe to specific security needs.

Fireproof 120 min for paper

- Fire resistant tested 120 minutes for paper according to UL 72 Class 350 2 Hr
- Three sided locking by means of steel bolts
- Hook-in profile on the hinge side
- Standard equipped with double bit key lock
- Height adjustable shelves
- Prepared for anchoring
- Color: light gray RAL 7035

Model specifications

Model	Outer dimensions (mm)	Internal dimensions (mm)	Volume (L)	Weight (kg)	Shelves
DPC 160	H859 W759 D605	H700 W600 D382	160 L	235 kg	1
DPC 240	H1209 W759 D605	H1050 W600 D382	240 L	315 kg	2
DPC 400W	H1209 W1160 D605	H1050 W1000 D382	401 L	500 kg	2
DPC 320	H1559 W759 D605	H1400 W600 D382	321 L	395 kg	3
DPC 400T	H1909 W759 D605	H1750 W600 D382	401 L	470 kg	4
DPC 670	H1909 W1160 D605	H1750 W1000 D382	670 L	650 kg	4