Atelier Boonen - ATB W wall safe



Additional information

brand: ATB Safes

ATB W – Certified wall safe Grade 1 (EN 1143-1, ECB·S)

The ATB W is a Grade 1 wall safe, tested and certified by ECB·S according to the European standard EN 1143-1. The safe is designed to be built into a wall or — better still — embedded in concrete, so that the wall itself becomes part of the protection.

The door of the ATB W has a total thickness of 85 mm, built up from multi-layered steel plates with a front panel and frame in 12 mm steel. The door features four-sided locking with moving steel bolts on all four sides, including the hinge side. The hinges are internal and allow a door opening of slightly more than 90°. The lock and boltwork are protected by additional armour plating and a passive blocking system.

The handle is fully recessed into the door and sits flush with the surface. Depending on the lock type, certain code locks can also be fully integrated, allowing the safe to be built in without anything protruding — discreetly concealed behind a painting, wall panel or cabinet door.

As standard, the ATB W is equipped with a double-bitted key lock. Optionally, versions are available with a mechanical combination lock or an electronic code lock, with emergency key or backlit keypad if desired.

The ATB W is available in five models from 12 to 85 litres, with removable, height-adjustable shelves — one or two depending on the model. From the same family, the ATB BT floor safe, also Grade 1, is for those who prefer building into the floor rather than the wall.

Teaser

See also our other built-in safes or read how to approach buying a safe in Belgium, with delivery and installation by our own team.

Burglary resistant class 1
Indication value storage class 1: € 10 000 cash or € 20 000 valuables

- Tested and certified by ECB·S in accordance with the European standard EN 1143-1, Grade I.
- Multi-walled door, front panel and frame in 12 mm steel, total thickness 85 mm.
- Four-sided locking with moving steel bolts on all four sides.
- Internal hinges; door opening of slightly more than 90°.
- Lock and boltwork protected by additional armour plating and a passive blocking system.
- As standard with double-bitted key lock.

- Height-adjustable shelves.
- Colour: light grey RAL 7035 or anthracite grey RAL 7024.

Model specifications

Model	Outer dimensions (mm)	Internal dimensions (mm)	Volume (L)	Weight (kg)	Shelves
W 10	H330 W390 D260	H230 W303 D166	12 L	34 kg	1
W 20	H330 W490 D260	H230 W403 D166	15 L	41 kg	1
W 30	H430 W490 D383	H330 W403 D289	38 L	57 kg	1
W 50	H630 W490 D383	H530 W403 D289	62 L	70 kg	2
W 70	H830 W490 D383	H730 W403 D289	85 L	89 kg	2