

Atelier Boonen - Sistec ES I safe



Additional information

Sistec Eurosafe ES I - Burglary-resistant safe (EN 1143-1 Grade 1, ECB-S)

The Sistec Eurosafe ES I is a burglary-resistant class 1 safe, certified according to EN 1143-1 and approved by ECB-S. This Sistec safe provides a reliable entry-level solution within the certified safe segment for private and professional use.

The Sistec Eurosafe ES I safe features a multi-wall steel construction with burglary-resistant filling and is equipped with a 10 mm solid steel door plate. The locking mechanism consists of a three-way locking system with solid steel bolts. Manganese steel drill protection secures the lock area, while a passive relocker automatically blocks the locking system in the event of an attack.

The recessed door and internal hinges prevent direct attacks on both the hinge and locking sides. The compact design makes this safe particularly suitable for discreet integration in walk-in wardrobes or cabinets.

As standard, the Sistec Eurosafe ES I is fitted with an EN 1300-certified double-bitted key lock. Optional versions are available with a mechanical combination lock or an electronic code lock, focused on simple and fast daily operation.

Anchoring through the floor or rear wall is possible. Fixing materials are included.

Burglary-resistant Class 1

Indicative value storage class 1: € 10 000 cash or € 20 000 valuables

- Tested and certified by ECB.S in accordance with European standard EN 1143-1 in Grade 1.
- Multi-walled construction of walls and door.
- Four-sided locking by means of steel bolts.
- Internal hinges.
- Standard equipped with double bit key lock
- Maximum door opening : 90

- Shelves adjustable in height
- Anchor holes provided in the back and bottom
- Color: gray RAL7035

Model specifications

Model	Outer dimensions (mm)	Internal dimensions (mm)	Volume (L)	Weight (kg)	Shelves
ES I 330	H330 W450 D400	H240 W360 D300	26 L	59 kg	1
ES I 450	H450 W450 D400	H360 W360 D300	39 L	72 kg	1
ES I 570	H570 W450 D400	H480 W360 D300	52 L	86 kg	1
ES I 690	H690 W450 D400	H600 W360 D300	65 L	100 kg	2
ES I 850	H850 W450 D400	H760 W360 D300	82 L	117 kg	2