Atelier Boonen - Salvus Bergamo - Class IV safe



Additional information

brand: Salvus safes

Salvus Bergamo – Burglary- and fire-resistant safe (Grade 4, LFS 30P)

The Salvus Bergamo is a certified burglary- and fire-resistant safe, tested in accordance with EN 1143-1 Grade 4 and certified by ECB·S. Fire protection in accordance with EN 15659 – LFS 30P provides protection for paper documents at temperatures of up to 850 °C for 30 minutes.

The safe construction features a multi-wall steel structure, with the interspaces filled with Ultra High Performance Concrete (UHPC). This high-performance concrete, reinforced with internal reinforcement and stiffening elements, contributes to a very high resistance to mechanical and thermal burglary methods.

The door is locked on four sides: three sides with solid steel bolts and, on the hinge side, an internal hook profile that engages into the body over the full height of the door. Attacks on the hinges therefore have no effect. External hinges allow a door opening angle of up to 180°.

In the event of a targeted attack on the lock or the door, a passive relocking system with a glass plate is automatically activated. This glass plate immediately triggers the blocking mechanism, securing the locking system. The system operates entirely mechanically and requires no external activation or power supply.

In accordance with the requirements of EN 1143-1 Grade 4, the Salvus Bergamo is standard equipped with two EN 1300-certified class B locks. Depending on the application, the safe can be configured with double-bitted key locks, mechanical combination locks, electronic keypad locks, or a combination of different lock

types. Certain electronic locks can optionally be fitted with an emergency key, as well as time delay and time window functions.

The range is available in multiple sizes from approximately 62 litres. Thanks to its high level of protection and controlled external dimensions, the Salvus Bergamo is suitable for professional applications where an increased level of security is required.

The finish is executed in anthracite grey RAL 7024.
The range is standard prepared for floor and wall anchoring.

See also our other fire resistant safes or read how to approach buying a safe in Belgium, with delivery and installation by our own team.

Fire resistant 30 min for paper
Burglary resistant class 4
Indication value storage class 4: € 75 000 cash or € 150 000 valuables

- Tested and certified by ECB·S in accordance with the European standard EN 1143-1, Grade IV.
- Fire tested for 30 minutes for paper according to EN 15659 LFS 30P.
- Multi-walled construction of walls and door, filled with UHPC, reinforced with internal armatures.
- Four-sided locking: solid steel bolts on three sides and an internal hook profile engaging into the body over the full height of the door.
- Passive relocking system with glass plate, blocking the locking mechanism in the event of an attack on the lock or door.
- External hinges; door opening up to 180°.
- Equipped as standard with 2 double-bitted key locks; mechanical combination or electronic code locks possible.
- Height-adjustable shelves.
- Prepared as standard for floor and wall anchoring.
- Colour: anthracite grey RAL 7024.

Model specifications

Model	Outer dimensions (mm)	Internal dimensions (mm)	Volume (L)	Weight (kg)	Shelves
Salvus Bergamo 1	H550 W550 D520	H423 W435 D336	62 L	300 kg	1
Salvus Bergamo 2	H670 W550 D520	H543 W435 D336	79 L	366 kg	1
Salvus Bergamo 3	H840 W550 D520	H713 W435 D336	104 L	411 kg	1
Salvus Bergamo 4	H1010 W550 D520	H883 W435 D336	129 L	505 kg	2
Salvus Bergamo 5	H1200 W550 D520	H1073 W435 D336	157 L	585 kg	2
Salvus Bergamo 6	H1200 W850 D660	H1053 W715 D466	351 L	974 kg	2
Salvus Bergamo 7	H1320 W680 D550	H1173 W545 D356	228 L	805 kg	3
Salvus Bergamo 8	H1510 W680 D550	H1363 W545 D357	295 L	900 kg	3