

Atelier Boonen - Salvus Bergamo - Class IV safe



Additional information

Salvus Bergamo - Burglary- and fire-resistant safe (Grade 4, LFS 30P)

The Salvus Bergamo is a certified burglary- and fire-resistant safe, tested in accordance with EN 1143-1 Grade 4 and certified by ECB-S. Fire protection in accordance with EN 15659 – LFS 30P provides protection for paper documents at temperatures of up to 850 °C for 30 minutes.

The safe construction features a multi-wall steel structure, with the interspaces filled with Ultra High Performance Concrete (UHPC). This high-performance concrete, reinforced with internal reinforcement and stiffening elements, contributes to a very high resistance to mechanical and thermal burglary methods.

The door is equipped with a three-sided locking system using solid steel bolts. On the hinge side, an internal interlocking profile is integrated over the full height of the door, rendering attacks on the hinges ineffective. External hinges allow a door opening angle of up to 180°.

In the event of a targeted attack on the lock or the door, a passive relocking system with a glass plate is automatically activated. This glass plate immediately triggers the blocking mechanism, securing the locking system. The system operates entirely mechanically and requires no external activation or power supply.

In accordance with the requirements of EN 1143-1 Grade 4, the Salvus Bergamo is standard equipped with two EN 1300-certified class B locks. Depending on the application, the safe can be configured with double-bitted key locks, mechanical combination locks, electronic keypad locks, or a combination of different lock types. Certain electronic locks can optionally be fitted with an emergency key, as well as time delay and

time window functions.

The range is available in multiple sizes from approximately 62 litres. Thanks to its high level of protection and controlled external dimensions, the Salvus Bergamo is suitable for professional applications where an increased level of security is required.

The finish is executed in anthracite grey RAL 7024.

The range is standard prepared for floor and wall anchoring.

Fireproof 30 min for paper

Burglary resistant class 4

Indicated value retention class 4: € 75 000 cash or € 150 000 valuables

- Tested and certified by ECB.S according to European standard EN 1143-1 Grade IV
- Fire resistant tested 30 minutes for paper according to EN 15659 LFS 30P
- Three-sided locking by means of steel bolts
- Hook-in profile on the hinge side
- Standard equipped with 2 double bit locks
- Height adjustable shelves
- Prepared for anchoring
- Color: anthracite gray RAL 7024

Model specifications

Model	Outer dimensions (mm)	Internal dimensions (mm)	Volume (L)	Weight (kg)	shelves
<u>Bergamo 1</u>	H550 W550 D520	H423 W435 D336	62 L	300 kg	1
<u>Bergamo 2</u>	H670 W550 D520	H543 W435 D336	79 L	366 kg	1
<u>Bergamo 3</u>	H840 W550 D520	H713 W435 D336	104 L	411 kg	1
<u>Bergamo 4</u>	H1010 W550 D520	H883 W435 D336	129 L	505 kg	2
<u>Bergamo 5</u>	H1200 W550 D520	H1073 W435 D337	179 L	533 kg	2
<u>Bergamo 6</u>	H1200 W850 D660	H1053 W715 D467	387 L	893 kg	2
<u>Bergamo 7</u>	H1320 W680 D550	H1173 W545 D357	255 L	793 kg	3
<u>Bergamo 8</u>	H1510 W680 D550	H1363 W545 D357	295 L	856 kg	0