

Atelier Boonen - Asecos ION-PRO-90



Additional information

Asecos ION-PRO 90 - Safety cabinet for storing and charging lithium batteries

The Asecos ION-PRO 90 is a certified and reliable safety cabinet for the passive and active storage of lithium-ion batteries. It offers 90 minutes of fire resistance, both from the outside and the inside, tested to meet EN 14470-1, EN 1363-1, and the stringent VDMA 24994 grade I specification. Ideal for workshops, charging rooms and technical environments.

An integrated ventilation unit prevents heat build-up during charging. Smoke and temperature sensors detect early signs of fire and activate alarms via a LED display, with both acoustic and visual signals. The alarm can be forwarded to a building management system via volt-free contacts.



Isolated shelving prevents fire from spreading between storage levels. A three-point locking system ensures the doors stay closed during fire incidents. The integrated transport base allows for internal relocation or emergency evacuation. For added safety, an automatic fire suppression system is available as an option.

- 90-minute fire resistance (outside-in), tested to EN 14470-1
- 90-minute fire resistance (inside-out), tested to EN 1363-1
- Certified according to VDMA 24994 grade I (thermal runaway fire tested)
- CE compliant
- For passive and active storage of lithium-ion batteries
- Isolated shelving prevents fire spread between battery levels
- LED display with visual and acoustic alarm
- Smoke and temperature sensors with BMS alarm forwarding
- Integrated ventilation unit reduces heat build-up
- High-quality grounded sockets inside the fireproof compartment
- Optional automatic fire suppression system
- Volt-free alarm contacts for connection to a monitoring center
- Three-point locking system operable with one hand
- Integrated transport base for internal movement or evacuation Total power capacity:
 - Single-phase: 16 A / 3.68 kW
 - Three-phase: 3 × 16 A / 11.04 kW
- Number of sockets per strip: 8



Model specifications

Model	Outer dimensions (mm)	Internal dimensions (mm)	Volume (L)	Weight (kg)	Shelves
IO90.195.120.PC.WDC	H2114 W1196 D615	H1647 W1050 D503	869 L	531 kg	0