

Atelier Boonen - ATB Sentinel III Safe



Additional information

Sentinel III - Burglar-resistant safe, Grade 3 (ECB·S certified)

The Sentinel III safe is a robust free-standing model, certified by ECB·S according to EN 1143-1, Grade 3.

The body and door are built from a multi-walled steel construction, filled with 50 mm of reinforced concrete. A fire-resistant sealing around the door frame provides additional protection against heat.

The door is secured by a solid three-way locking system with chrome-plated active bolts and fixed bolts on the hinge side. An internal relocking device ensures the safe is automatically blocked in case of an attempted break-in. The safe can be firmly anchored to the floor and/or wall through the prepared fixing bolos.

The Sentinel III safe is available with a certified key lock (VdS Class 2) or with an electronic code lock. The series includes 9 models with capacities ranging from 30 to 446 litres.

The Sentinel III safe is a reliable, durable and well-engineered solution for those requiring a certified Grade 3 burglar-resistant safe.

Fire resistant 30 min for paper Burglary resistant Class 3

Indication of value storage Class 3: € 45 000 cash or € 90 000 valuables

- Tested and certified by ECB.S in accordance with European standard EN 1143-1 in Grade III
- Fire resistant tested 30 minutes for paper according to EN15659 LFS 30P
- Multi-walled door and body filled with a special composite material
- Four-sided locking by means of steel bolts
- Lock and frame protected with additional armoring and passive locking system
- Standard equipped with double bit key lock



- Height adjustable shelves
- Prepared for floor and wall anchoring.
- Color: chocolate brown



Model specifications

	, ,			, ,	
Model	Outer dimensions (mm)	Internal dimensions (mm)	Volume (L)	Weight (kg)	Shelves
<u>III 37</u>	H370 W480 D450	H270 W380 D290	30 L	160 kg	1
<u>III 50</u>	H500 W480 D450	H400 W380 D290	44 L	196 kg	1
<u>III 65</u>	H650 W550 D550	H550 W450 D390	97 L	300 kg	2
<u>III 80</u>	H800 W600 D550	H700 W500 D390	137 L	376 kg	3
<u>III 95</u>	H950 W600 D550	H850 W500 D390	166 L	435 kg	3
<u>III 110</u>	H1100 W650 D550	H1000 W550 D390	215 L	518 kg	4
<u>III 125</u>	H1250 W650 D550	H1150 W550 D390	246 L	574 kg	5
<u>III 140</u>	H1400 W650 D650	H1300 W550 D490	350 L	680 kg	5
<u>III 150</u>	H1500 W750 D650	H1400 W650 D490	446 L	855 kg	6