

Atelier Boonen - ATB Sentinel V safe



Additional information

Sentinel V - Burglar-resistant safe, Grade 5 (ECB-S certified)

The Sentinel V safe is a free-standing model, certified by ECB-S according to EN 1143-1, Grade 5. This safe provides very high burglary resistance thanks to its extremely robust construction.

The body and door are built from a fully welded multi-walled steel construction, with a protective layer of

heavy-duty reinforced concrete, 80 to 100 mm thick. A fire-resistant sealing around the door frame offers additional protection against heat.

The door is fitted with a strong three-way locking system with chrome-plated active bolts of Ø32 mm (40 mm in larger models) and fixed bolts on the hinge side. An internal relocking system automatically blocks the safe in case of an attempted break-in. Hardened steel plates (armour plates) protect locks and bolts against drilling and striking.

The Sentinel V safe is supplied as standard with two key locks, EN 1300 Class B. Optional mechanical and electronic locks are available, including time lock and audit functions. The safe can be firmly anchored to floor or wall through the prepared fixing holes and comes in a dark grey finish.

The series includes 7 models with capacities from 114 to 514 litres.

The Sentinel V safe is a durable and technically advanced solution for those requiring a certified Grade 5 burglar-resistant safe.

Burglary resistant class 5

Indicative value retention class 5: € 125 000 cash or € 250 000 valuables

- Tested and certified by ECB.S according to the European standard EN 1143-1 Grade V
- Three-sided locking by means of steel bolts
- Fixed bolts on the hinge side, making any attack on the hinges ineffective
- Standard equipped with two double bit key locks
- Height adjustable shelves
- Prepared for anchoring
- Color: dark gray

Model specifications

Model	Outer dimensions (mm)	Internal dimensions (mm)	Volume (L)	Weight (kg)	Shelves
V 70	H700 W700 D600	H540 W540 D390	114 L	571 kg	1
V 85	H850 W700 D700	H690 W540 D490	182 L	726 kg	2
V 100	H1000 W700 D700	H840 W540 D490	222 L	813 kg	3
V 130	H1300 W700 D700	H1140 W540 D490	302 L	987 kg	3
V 150	H1500 W700 D700	H1340 W540 D490	355 L	1103 kg	4
V 165	H1650 W700 D700	H1490 W540 D490	394 L	1190 kg	4
V 180	H1800 W800 D700	H1640 W640 D490	514 L	1395 kg	5