Atelier Boonen - Asecos C-LINE



Additional information

brand: Asecos

Asecos C-LINE – Cabinet for non-flammable chemicals, acids and alkalis

The Asecos C-LINE is designed for storing non-flammable hazardous substances in workrooms: acids, alkalis and toxic substances. The cabinet is not fire-resistant; flammable liquids belong in a safety cabinet to EN 14470-1. The C-LINE is welded, finished with a scratch-resistant textured paint and compliant with EN 16121 and EN 16122.

You store different hazardous substances separately in up to four compartments, each fitted out individually and labelled for the substance stored. Pull-out shelves with plastic sumps collect leakage and give a good overview; with a perforated insert, the bottom sump serves as an extra storage level. For a small quantity of flammable liquids, the cabinet can optionally be fitted with a type 30 safety box.

The C-LINE comes in three widths and two heights, with hinged doors, hinged doors with fixed window or space-saving folding doors. The doors lock with a profile cylinder or cylinder lock. The cabinet has natural ventilation at the bottom and is ready for connection (DN 75) to mechanical extraction. You choose from

seven door colours.

Which substances must not be stored together and how to separate acids and alkalis is explained in our guide to the storage of hazardous substances.

To keep different substances apart in one cabinet, see the asecos C-LINE MultiRisk with 3 or 4 lockable compartments. If a duct to the outside is not possible, there is the asecos CX-LINE with a built-in recirculation filter.

See also our other cabinets for acids and alkalis, supplied and installed by our own team in Belgium.

- Cabinet for non-flammable chemicals, acids, alkalis and toxic substances; not fire-resistant
- Compliant with EN 16121 and EN 16122
- Up to 4 separate compartments, individually fitted out, with labelling system
- Pull-out shelves with plastic sumps; perforated insert for the bottom sump
- Optional: type 30 safety box for small quantities of flammable liquids
- Three widths and two heights
- Hinged doors, hinged doors with fixed window or folding doors
- Profile cylinder or cylinder lock
- Natural ventilation at the bottom, ready for DN 75 connection to mechanical extraction
- Seven door colours

Model specifications

Model	Outer dimensions (mm)	Internal dimensions (mm)	Volume (L)	Weight (kg)	Shelves
Asecos CS.195.054	H1950 W545 D520	H1835 W486 D493	440 L	74 kg	0
Asecos CS.195.081	H1950 W810 D520	H1835 W751 D493	679 L	94 kg	0
Asecos CS.195.105	H1950 W1055 D520	H1835 W996 D493	901 L	110 kg	0
Asecos CS.195.105.FD	H1950 W1055 D520	H1835 W996 D493	901 L	115 kg	0
Asecos CS.110.054	H1105 W545 D520	H990 W486 D493	237 L	52 kg	0
Asecos CS.110.105.FD	H1105 W1055 D520	H990 W996 D493	486 L	82 kg	0